



# Air Pure



## Technical information

Version one 05.07

### Colours available

Elite white with blue panel  
Elite white with grey panel  
Stainless steel

### Dimensions

#### Elite

Width 165 mm  
Height 230 mm  
Depth 110 mm  
(to maximum ellipse)

#### Stainless Steel

Width 160 mm  
Height 250 mm  
Depth 90 mm

### Construction

Elite - UV stabilised ABS plastic  
Stainless steel - Plated stainless steel

### Power supply

100 - 240V  
12 watts (via 5A switched, fused spur)  
50/60 Hz single phase

### Weight

Elite  
0.9 kg  
Stainless steel  
1 kg

### Ozone output

1.6 - 4.0 mg/hour ( $\pm 20\%$ )

### Timer settings

24 hour display  
7 day, 8 ON/OFF periods per day

## Additional information

### Installation

- Unit must only be connected to the electricity supply by a qualified electrician
- At least 30 cm below ceiling
- Near cubicles or urinals

### Avoid installing

- Within reach of general public
- Near to open windows, above radiators, near ventilation inlets/outlets
- Directly above cubicles or urinals
- 24-hour operating washrooms with permanent attendants
- Washrooms less than 10 cubic metres

### Servicing

Unit must be serviced by a fully trained technician



Caring for clean environments